



Technical Specifications

Package Includes:..... Motor, Pump Tube, Hose, Storage Bracket, Flow Meter, Barrel Adapter & Hand Nozzle

Motor Type:..... TEFC (IP54)

Pump Tube Material:..... PVDF, Hastelloy C-276, Carbon Graphite

Immersion Length:..... 39" (1000 mm) or 47" (1200 mm)

Discharge Hose:Modified Cross-Link Polyethylene, 6 ft (1,8 m), 1" (25 mm) I.D.

Hand Nozzle Material: PVDF, Viton

Flow Meter Material: PVDF, Viton, Halar, Ceramic

Flow Meter Type:.....Digital / Battery Powered Totalizer

Maximum Flow Rate:..... 13.5 GPM (51 LPM) *based on water*

Maximum Viscosity: 300 cps (mPas)

Maximum Temperature: 175° F (80° C)

Shipping Weight:..... 31 lbs. (14,06 kg)

RECOGNIZED COMPONENT



DRUMS

Package P/N	Motor	Volts	Pump Tube
9510	SP-ENC-V	110V	SP-PVDF-39
9511	SP-ENC-2-V	220V	SP-PVDF-39

TANKS

Package P/N	Motor	Volts	Pump Tube
9512	SP-ENC-V	110V	SP-PVDF-47
9513	SP-ENC-2-V	220V	SP-PVDF-47



Warning: This pump is not suitable for use with Flammable/Combustible liquids.

*Note: When pumping viscosities over 1,000 cps, pump must be used intermittently to avoid potential premature failure and/or damage.